



VIBROSCREEN

Portable screeners

by **VT** | VIBROTECH



SCM-40C

Up to
3 cubic
yards
bucket

Optimized for
performance,
engineered to last.

GREAT QUALITY, GREAT VALUE!

- Heavy duty construction
- Portable equipment
- Up to 100 cubic yards per hour
- Low maintenance
- Reversible shaker head for better screening effect
- Quick screen change

vibroscreen.ca

819 362-8871

info@vibroscreen.ca



VIBROSCREEN

Portable screeners

by **VIBROTECH**

GRIZZLY

PINTLE HOOK

MODEL SCM-40C

Up to 100
cubic yards
per hour



CAPACITY

Maximum single load	Up to 3 cubic yards
Cycle time (average)	30 seconds
Shaker head decks	2
Screening area	71" x 82" (40 sq-ft)

TOWING

Hitch type	Fifth wheel
Axle type	Single axle, double wheels
Suspension	None
Brakes	Air
Landing gear	Hydraulic
Lights and mud flaps	Included

ENGINE

Manufacturer	Perkins
Type	Diesel, vertical, water cooled
Tank	84 litres (22 gal)
Fuel autonomy	Up to 8 hours
Power	67 HP
Number of cylinders	4
Cold starting aid	Glow plug
Electric starter	Included
Alternator	Included

OPTIONS AVAILABLE

- Wings plates extensions (included)
- Hydraulic grizzly
- Pintle hook hitch type
- Flexmat screen

WEIGHT

Gross weight	18 820 lbs (8536 kg)
Tongue weight	4775 lbs (2165 kg)

HYDRAULICS

Control valves	Shaker head (forward - reverse) Front jack cylinder Axle cylinder Conveyor (start-stop, open-close) Hydraulic cooler
Cooling	

WARRANTY

Equipment	12 months
Motor	24 Months (Perkins)

WORKING DIMENSIONS

Loading height	9'- 11"
Hopper width (feeding)	9'- 4"
Underneath capacity (bucket width)	45'- 5"
Free height (under conveyor)	10'- 9"
Discharge belt width	42"

FREIGHT DIMENSIONS

Total height on wheels	10'- 9"
Total length	34'- 1"
Total width	8'- 0"