



VIBROSCREEN

Portable screeners

by **VT | VIBROTECH**



SCM-75

Up to
6 cubic
yards
bucket

Optimized for
performance,
engineered to last.

GREAT QUALITY, GREAT VALUE!

- Heavy duty construction
- Portable equipment
- Up to 300 cubic yards per hour
- Low maintenance
- Reversible shaker head for better screening effect
- Quick screen change

vibroscreen.ca

819 362-8871

info@vibroscreen.ca



VIBROSCREEN

Portable screeners

by **VIBROTECH**

PUNCH PLATES (TOP SCREEN)


WINGS PLATES EXTENSIONS

WEAR PLATES (OVER'S SIDE)

STEEL SKIRT FOR WHEELS

MODEL SCM-75

Up to 300 cubic
yards / hour



CAPACITY

Maximum single load	Up to 6 cubic yards
Cycle time (average)	30 seconds
Shaker head decks	2
Screening area	119" x 90" (75 sq-ft)

TOWING

Hitch type	Fifth wheel
Axle type	Single axle, double wheels
Suspension	None
Brakes	Air
Landing gear	Hydraulic
Lights and mud flaps	Included

ENGINE

Manufacturer	Perkins
Type	Diesel, vertical, water cooled
Tank	84 litres (22 gal)
Fuel Autonomy	Up to 10 hours
Power	50 HP
Number of cylinders	4
Cold starting aid	Glow plug
Electric starter	Included
Alternator	Included

OPTIONS AVAILABLE

Wings plates extensions	Steel skirt for wheels
Hydraulic grizzly	Flexmat screen
Wear plate (over's side)	Punch plates (top screen)

WEIGHT

Gross weight	21 641 lbs (9816 kg)
Tongue weight	8541 lbs (3874 kg)

HYDRAULICS

Control valves	Shakerhead (forward - reverse) Front jack cylinder Axle cylinder
Cooling	Hydraulic cooler

WARRANTY

Equipment	12 Months
Motor	24 Months (Perkins)

WORKING DIMENSIONS

Loading height	11'- 0"
Hopper width (feeding)	12'- 6"
Underneath capacity (bucket width)	12'- 6"

FREIGHT DIMENSIONS

Total height on wheels	11'- 11"
Total length	26'- 4"
Total width	8'- 4"